US009638437B2

(12) **United States Patent**
Hong et al.

(10) **Patent No.: US 9,638,437 B2**
(45) **Date of Patent: May 2, 2017**

(54) **STRUCTURE FOR FIXING COMPRESSOR FOR DEHUMIDIFIER**

(71) Applicants: **COWAY CO., LTD**, Chungcheong-nam-do (KR); **WINIX INC.**, Gyeonggi-do (KR)

(72) Inventors: **Hyun-Jin Hong**, Seoul (KR); **Chan-Jung Park**, Seoul (KR); **Sang-Woo Kang**, Seoul (KR)

(73) Assignee: **COWAY CO., LTD.**, Chungcheong-nam-do (KR)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 235 days.

(21) Appl. No.: **14/382,925**

(22) PCT Filed: **Mar. 12, 2013**

(86) PCT No.: **PCT/KR2013/001957**
§ 371 (c)(1),
(2) Date: **Sep. 4, 2014**

(87) PCT Pub. No.: **WO2013/141512**
PCT Pub. Date: **Sep. 26, 2013**

(65) **Prior Publication Data**

US 2015/0047383 A1 Feb. 19, 2015

(30) **Foreign Application Priority Data**

Mar. 20, 2012 (KR) 10-2012-0028511

(51) **Int. Cl.**
F24F 1/00 (2011.01)
F24F 13/24 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC ***F24F 13/24*** (2013.01); ***F04D 29/668*** (2013.01); ***F24F 13/32*** (2013.01); ***F25D 23/006*** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC F24F 13/24; F24F 13/32; F24F 2003/144; F04D 29/668; F25D 23/006; F25B 2500/13
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,643,386 A 2/1987 Chastine
6,011,336 A * 1/2000 Mathis F16F 1/376 248/628
(Continued)

FOREIGN PATENT DOCUMENTS

CN 1991168 7/2007
CN 101910763 12/2010
(Continued)

OTHER PUBLICATIONS

International Search Report. PCT/KR2013/001957 (2 Pages) Dated: May 27, 2013.
(Continued)

Primary Examiner — Anita M King
(74) *Attorney, Agent, or Firm* — Dority & Manning, P.A.

(57) **ABSTRACT**

There is provided a compressor fixing structure capable of preventing vibrations from a compressor from being spread to the entirety of a product in which the compressor is installed. The compressor fixing structure includes: a plurality of support units disposed to have a polygonal structure and protruded from a bottom surface; a support unit anti-vibration rib protruded from a perimeter of each of the plurality of support units; and an outer anti-vibration rib surrounding the entirety of the plurality of support units and protruded from a bottom surface. Spreading of vibrations from a compressor installed in a product is minimized, reducing vibrations and noise generated by the compressor when the compressor is driven.

9 Claims, 4 Drawing Sheets